

# 2009 Update of the NREL biomass-to-ethanol biochemical process design report




**IEA Bioenergy  
Conference  
Vancouver**

**Dave Humbird  
Ling Tao**

**with Harris Group, Inc.**


**August 25, 2009**

# Technoeconomic Modeling



- Modeling is rigorous and detailed with clear and transparent assumptions
- Assumes  $n^{\text{th}}$ -plant equipment costs
- Discounted cash-flow ROR calculation includes (e.g.) return on investment, equity payback, and taxes
- Determines the minimum ethanol selling price required for zero NPV at plant end-of-life (MESP > COP)

# 2002 Biochemical Design Report



June 2002 • NREL/TP-510-32438

## Lignocellulosic Biomass to Ethanol Process Design and Economics Utilizing Co-Current Dilute Acid Prehydrolysis and Enzymatic Hydrolysis for Corn Stover

A. Aden, M. Ruth, K. Ibsen, J. Jechura, K. Neeves, J. Sheehan, and B. Wallace  
National Renewable Energy Laboratory

L. Montague, A. Slayton, and J. Lukas  
Harris Group  
Seattle, Washington



National Renewable Energy Laboratory

1617 Cole Boulevard  
Golden, Colorado 80401-3393

NREL is a U.S. Department of Energy Laboratory  
Operated by Midwest Research Institute • Battelle • Bechtel  
Contract No. DE-AC36-99-GO10337

- Conceptual design of a 2,200 dry ton/day commercial plant
- Documents one possible technology package for cost-effective ethanol
- Establishes a benchmark for comparison of other technology options
- Quantifies economic impact of research progress and helps set goals
- Permits better industrial collaboration
- Has been reviewed by industry, academia, and government

# Motivation for the 2009 design report update

---

- Incorporate recent research learning into 2012 model
- Optimize design
  - Water reduction and power utilization
  - Consider different configurations
- Update equipment decisions
  - Detailed vendor quotes for key unit operations
  - New costs for standard equipment in 2009\$
- Revisit major assumptions
- Improve model stability and usability
- ***Significant changes made to all process areas***


# Corn stover feedstock composition

- 2002 feedstock composition was an average of 9 samples from two batches
- Glucan was determined to be too high based on a 2007-2008 round-robin study
- 2009 composition is based on a single sample
- Economic implications
  - Less total sugar = lower yield of 81.5 gal/ton vs 90 in 2002
  - Lower lignin = smaller electricity credit
  - Extractives component is essentially inert in the model

<i>Component Dry wt%</i>	<i>2002</i>	<i>2009</i>
Glucan	37.4	33.12
Xylan	21.1	20.64
Lignin	18	11.62
Ash	5.2	4.78
Acetate	2.9	2.77
Protein	3.1	1.45
Extractives	4.7	17.88
Arabinan	2.9	3.87
Galactan	2	1.53
Mannan	1.6	0
Unknown Soluble Solids	1.1	2.35
Total	100	100


Feedstock cost is \$50.90/dry ton, including all handling and transport to pretreatment

# Dilute-acid pretreatment



- **2002:**
  - Anco-Eaglin reactor design (based on a rendering unit)
  - Solid/liquid separation of pretreated material with lime conditioning on the liquid only
- **2009:**
  - Purpose-designed reactor from Andritz, Inc.
  - Whole-slurry conditioning with ammonia
  - Secondary hold step converts xylose oligomers to monomers

# Enzymatic hydrolysis & fermentation




- **2002:**
  - Separate hydrolysis and fermentation in a continuous train
- **2009:**
  - High-solids first-stage hydrolysis reactor (targeting 20 wt% total solids)
  - Hydrolysis continues in a batch reactor
  - Fermentation is initiated in the same reactor before hydrolysis is complete (hybrid SHF/SSF)




# Solids loading at enzymatic hydrolysis

Glucose Yield as a Function of Enzyme Dose  
Whole-Slurry, 48° C Incubation Temperature




- There is an economic benefit to performing hydrolysis at higher solids loading
- Enzyme activity falls off at higher solids loading but enzyme dose can be increased to overcome lower conversion
- For a constant ethanol yield, there is an optimum %solids that depends on the enzyme price
- Lower enzyme prices (i.e. 2012 DOE target prices) push the hydrolysis optimum operating regime toward “high solids” loading (>20%)






# On-site enzyme production



- **2002:**
  - Purchased enzyme model with fixed cost contribution (\$0.12/gal)
- **2009:**
  - Detailed model of a smallish enzyme production facility
  - Aerobic growth of *T. reesei* on glucose substrate
  - Genencor's economic sophorose conversion step is assumed
  - Provides more transparency on the actual economics of enzyme production


# Changes and challenges in the back-end

## Overliming




- Inorganic compounds are removed as a wet solid
- Significant xylose sugar is lost with the solid
- This solid is probably toxic and would require remediation before disposal

## Whole-slurry NH<sub>3</sub> conditioning




- Much simpler process; no solid-liquid separations required
- Minimal sugar losses
- Ammonia is expensive compared to lime
- Inorganic compounds stay in the process and wind up in the boiler

# Existing back-end process



# New back-end process



# Water demand reduction

- 2002 Water usage was ~6 gal/gal
  - High compared to corn dry mill and thermochemical ethanol
  - We feel an obligation to reduce this where possible
- >50% of water losses are from the cooling tower
  - Elimination of the evaporator system is a significant savings
- Other water-saving process changes have been identified
  - Elimination of condensing turbine (=lower electricity credit)
  - Air-cooled exchangers for major cooling water users
- 2 gal/gal has been demonstrated using all known water-saving measures
- The most economic of these measures will be implemented
- Sustainability metrics will be a focus of the design report (“LCA-ready”)

# Work remaining and timeline

- Oct 08 – Aug 09: Aspen model updated, Harris obtained quotes for major process equipment
- 8/4/09: Held a meeting with researchers and internal stakeholders to present the new process and get agreement on key design assumptions
  - Some significant changes were required in Aspen as a result
  - No additional non-standard equipment items
- Aug – Sep 09: Finish the Aspen, get remaining costs
- Sep 09: Report writing
- Oct – Nov 09: Peer review (reviewers needed)
- Dec 09: Issue NREL technical report

# Acknowledgements

## DOE's Office of the Biomass Program

<http://www.eere.energy.gov/biomass>

## NREL Biorefinery Analysis Team

– Andy Aden, Abhijit Dutta, David Hsu, Steve Phillips

## Speaker information:

[David.Humbird@nrel.gov](mailto:David.Humbird@nrel.gov)

<http://www.nrel.gov/biomass>



## References:

Feedstock: <http://www.inl.gov/bioenergy/uniform-feedstock>